




BD 3-6kW-RL1

Single Phase Hybrid Inverter (48V)



Lead-acid/
lithium
battery



Battery reverse
protection



IP65



Smart energy
management



Zero export
function
(integrated)



Natural cooling,
low noise



Charge/discharge
protection

	BD3KTL-RL1	BD3K6TL-RL1	BD4KTL-RL1	BD4K6TL-RL1	BD5KTL-RL1	BD6KTL-RL1
Input (PV)						
Max. PV Input Power	4.6kW		6kW		7kW	
Max. PV Input Voltage	550V					
MPP Voltage Range	125V ~ 500V					
Max. PV Input Current	12A					
Number of MPP Trackers / String per MPPT	2 / 1					
Output (AC)						
Max. Output Current	13A	16A	17.4A	20A	21.7A	26A
Rated Power	3kVA	3.6kVA	4kVA	4.6kVA	5kVA	6kVA
Rated Voltage	230V, L + N + PE					
Operating Voltage Range	176V ~ 270V					
Frequency	50Hz / 60Hz					
Power Factor	0.8 lagging~0.8 leading					
THDi	<3%					
Output (EPS)						
Rated Power	3kVA	3.6kVA	4kVA	4.6kVA	5kVA	6kVA
Rated Voltage	230Vac					
Rated Current	13A	16A	17.4A	20A	21.7A	26A
Rated Frequency	50Hz / 60Hz					
Automatic Switch Time	<20ms					
Overload Capability	110%, 30s / 120%, 10s / 150%, 0.02s					
THDU	<2%					
Battery						
Battery Voltage Range	40V ~ 58V					
Max. Charging Voltage	58V					
Charge / Discharge Current	95A / 62.2A	95A / 75A	95A / 83.3A	95A / 95.8A	95A / 104.2A	95A / 110A
Battery Type	Lithium / Lead-acid					
Communication	CAN / RS485					
Efficiency						
Max. DC Efficiency	97.60%					
European Efficiency	97.0%					
MPPT Efficiency	99.90%					
Battery Charge / Discharge Efficiency	95.0%					
Communication						
Display	LCD					
Communication	standard: RS485 / CAN / DRM optional: WIFI / 4G					
Standard Compliance						
Certificates	CE, TUV, SAA, NRS					
General Data						
Dimensions (W x H x D)	550 x 515 x 200 mm					
Weight	25kg					
Operation Temperature	-25°C ~ +60°C					
Cooling Method	Natural Cooling					
Protection Degree	IP65					
Noise Emission	<35dB					
Max. Operating Altitude	2000m					
Relative Humidity	0 ~ 95% (non-condensing)					
Topology	Transformerless					
Standby Power Consumption	< 3W					